

SURFACE MOUNTED INDOOR PROFILE

Architape A002M Indoor Luminaire Series

24VDC / 48VDC

IP20

MACADAM 3-STEP

5-YEAR WARRANTY

HIGH EFFICACY NICHIA

The A002M fixture is a simple yet perfect solution for any cove lighting application.

POWER RANGE

1.2 W/m – 18.2 W/m

LUMINOUS FLUX


23 lm/m – 2,765 lm/m

DIMENSIONS (W X H)

16 x 6 mm

SERVICE LIFETIME

L90B10 > 60kh



ARCHITAPE INDOOR LUMINAIRE SERIES

TESTED & CERTIFIED UNDER INTERNATIONAL STANDARDS




SCAN TO VIEW SERIES ONLINE

ENGINEERING, OPTICS & DIMENSIONS

ARCHITAPE A002M INDOOR LUMINAIRE SERIES

PHOTOMETRIC DISTRIBUTION


120°



Precision optical distribution engineered for homogeneous illumination, minimal glare, and superior exterior facade grazing and accent lighting.

DIMENSIONS & PROFILE SECTION

SECTION: 16 X 6 MM



OUTER DIMENSIONS	16 x 6 mm
INGRESS PROTECTION	IP20
PROFILE MATERIAL	Extruded aluminium profile · Surface horizontal mounting / Surface vertical mounting
ENCAPSULATION / COVER	Clear, Opal, Round opal, Square opal

ELECTRICAL & SYSTEM SPECS

OPERATING VOLTAGE	24VDC / 48VDC (Constant Voltage)
AVAILABLE WATTAGES	1.2 W/m – 18.2 W/m
COLOR CONSISTENCY	MacAdam 3-Step Ellipse (SDCM ≤ 3)
DIMMING PROTOCOLS	PWM, 0-10V, DALI-2 (DT6/DT8), Casambi
OPERATING TEMP	-25°C to +50°C
MAX CASE TEMP (TC)	Tc max 75°C
WARRANTY	5-Year System Guarantee
LED EMITTERS	Nichia High-Efficiency LEDs

SPECTRAL & FINISH OPTIONS

AVAILABLE CCT	1400K, 1600K, 1800K, 2000K, 2200K, 2500K, 2700K, 3000K, 3500K, 4000K, 5000K, 5700K, 6500K, 7000K, 8000K, RGB, RGBW
COLOUR FIDELITY	CRI 80, CRI 90, CRI 95
OPTICAL COVERS	Clear, Opal, Round opal, Square opal
HOUSING COLOURS	Anodised grey, Black

PART NUMBER DECODING LOGIC

[RANGE] - [TAPE] - [VOLTAGE] - [POWER] - [COLOUR] - [PROFILE] - [FINISH] - [COVER] - [EXIT] - [CABLE] - [LENGTH]

Example: AL-100-48-5-027-A002M-BK-SQ0-LEC-0M2-1010

• A002M: profile · Black finish · Square opal cover · PRO 100 48V Single Colour Indoor LED Tape · 2700K · 1010 mm

INSTALLATION & CUSTOM LENGTHS

STANDARD LENGTHS	1010 mm standard · 12 tape options: PRO 100 48V Single Colour, PRO 100 RGB, PRO 100 Single Colour, PRO 100 TW, PRO 112S Single Colour, PRO 175 Single Colour, PRO 20 Single Colour, PRO 50 RGB, PRO 50 RGBW, PRO 50 Single Colour, PRO 50 TW, PRO 70 TW
CUSTOM CUTTING	Factory custom lengths down to segment pitch
CABLE ENTRY / EXITS	Side, Back, or End exit with IP67 connectors
DRIVER TYPE	Independent Class II SELV 24V / 48V

ARCHITAPE A002M INDOOR LUMINAIRE SERIES – STANDARD MODEL
DIRECTORY

PAGE 3 OF
4

PART CODE	COVER	BEAM	POWER	CCT / COLOUR	CRI	FLUX	FINISH	DATASHEET
AL-100-48-5-030-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Black	PDF ↗
AL-100-48-5-030-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Anodised grey	PDF ↗
AL-100-48-5-030-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Black	PDF ↗
AL-100-48-5-030-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Anodised grey	PDF ↗
AL-100-48-5-030-A002M-BK-OPA-LEC-0M2-1010	Opal	120Å°	4.8 W/m	3000K	CRI 95	371 lm	Black	PDF ↗
AL-100-48-5-030-A002M-AG-OPA-LEC-0M2-1010	Opal	120Å°	4.8 W/m	3000K	CRI 95	371 lm	Anodised grey	PDF ↗
AL-100-48-5-030-A002M-BK-CLR-LEC-0M2-1010	Clear	120Å°	4.8 W/m	3000K	CRI 95	461 lm	Black	PDF ↗
AL-100-24-12-RGB-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Å°	11.5 W/m	RGB	—	479 lm	Black	PDF ↗
AL-100-24-12-RGB-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Å°	11.5 W/m	RGB	—	479 lm	Anodised grey	PDF ↗
AL-100-24-12-RGB-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Å°	11.5 W/m	RGB	—	479 lm	Black	PDF ↗
AL-100-24-12-RGB-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Å°	11.5 W/m	RGB	—	479 lm	Anodised grey	PDF ↗
AL-100-24-12-RGB-A002M-BK-OPA-LEC-0M2-1010	Opal	120Å°	11.5 W/m	RGB	—	354 lm	Black	PDF ↗
AL-100-24-12-RGB-A002M-AG-OPA-LEC-0M2-1010	Opal	120Å°	11.5 W/m	RGB	—	354 lm	Anodised grey	PDF ↗
AL-100-24-12-RGB-A002M-BK-CLR-LEC-0M2-1010	Clear	120Å°	11.5 W/m	RGB	—	441 lm	Black	PDF ↗
AL-100-24-5-030-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Black	PDF ↗
AL-100-24-5-030-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Anodised grey	PDF ↗
AL-100-24-5-030-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Black	PDF ↗
AL-100-24-5-030-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Anodised grey	PDF ↗
AL-100-24-5-030-A002M-BK-OPA-LEC-0M2-1010	Opal	120Å°	4.8 W/m	3000K	CRI 95	371 lm	Black	PDF ↗
AL-100-24-5-030-A002M-AG-OPA-LEC-0M2-1010	Opal	120Å°	4.8 W/m	3000K	CRI 95	371 lm	Anodised grey	PDF ↗
AL-100-24-5-030-A002M-BK-CLR-LEC-0M2-1010	Clear	120Å°	4.8 W/m	3000K	CRI 95	461 lm	Black	PDF ↗
AL-100-24-10-82765-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Å°	9.6 W/m	2700-6500K	CRI 80	1,343 lm	Black	PDF ↗
AL-100-24-10-82765-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Å°	9.6 W/m	2700-6500K	CRI 80	1,343 lm	Anodised grey	PDF ↗
AL-100-24-10-82765-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Å°	9.6 W/m	2700-6500K	CRI 80	1,343 lm	Black	PDF ↗
AL-100-24-10-82765-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Å°	9.6 W/m	2700-6500K	CRI 80	1,343 lm	Anodised grey	PDF ↗
AL-100-24-10-82765-A002M-BK-OPA-LEC-0M2-1010	Opal	120Å°	9.6 W/m	2700-6500K	CRI 80	994 lm	Black	PDF ↗
AL-100-24-10-82765-A002M-AG-OPA-LEC-0M2-1010	Opal	120Å°	9.6 W/m	2700-6500K	CRI 80	994 lm	Anodised grey	PDF ↗
AL-100-24-10-82765-A002M-BK-CLR-LEC-0M2-1010	Clear	120Å°	9.6 W/m	2700-6500K	CRI 80	1,236 lm	Black	PDF ↗
AL-112-24-5-030-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Black	PDF ↗
AL-112-24-5-030-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Anodised grey	PDF ↗
AL-112-24-5-030-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Black	PDF ↗
AL-112-24-5-030-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Å°	4.8 W/m	3000K	CRI 95	501 lm	Anodised grey	PDF ↗
AL-112-24-5-030-A002M-BK-OPA-LEC-0M2-1010	Opal	120Å°	4.8 W/m	3000K	CRI 95	371 lm	Black	PDF ↗
AL-112-24-5-030-A002M-AG-OPA-LEC-0M2-1010	Opal	120Å°	4.8 W/m	3000K	CRI 95	371 lm	Anodised grey	PDF ↗

ARCHITAPE INDOOR LUMINAIRE SERIES

ARCHITAPE A002M INDOOR LUMINAIRE SERIES – STANDARD MODEL DIRECTORY

PAGE 4 OF 4

PART CODE	COVER	BEAM	POWER	CCT / COLOUR	CRI	FLUX	FINISH	DATASHEET
AL-175-24-5-030-A002M-BK-OPA-LEC-0M2-1010	Opal	120Â°	4.8 W/m	3000K	CRI 95	371 lm	Black	PDF ↗
AL-175-24-5-030-A002M-AG-OPA-LEC-0M2-1010	Opal	120Â°	4.8 W/m	3000K	CRI 95	371 lm	Anodised grey	PDF ↗
AL-20-24-1-030-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Â°	1.2 W/m	3000K	CRI 95	125 lm	Black	PDF ↗
AL-20-24-1-030-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Â°	1.2 W/m	3000K	CRI 95	125 lm	Anodised grey	PDF ↗
AL-20-24-1-030-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Â°	1.2 W/m	3000K	CRI 95	125 lm	Black	PDF ↗
AL-20-24-1-030-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Â°	1.2 W/m	3000K	CRI 95	125 lm	Anodised grey	PDF ↗
AL-20-24-1-030-A002M-BK-OPA-LEC-0M2-1010	Opal	120Â°	1.2 W/m	3000K	CRI 95	92 lm	Black	PDF ↗
AL-20-24-1-030-A002M-AG-OPA-LEC-0M2-1010	Opal	120Â°	1.2 W/m	3000K	CRI 95	92 lm	Anodised grey	PDF ↗
AL-50-24-7-RGB-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Â°	7.2 W/m	RGB	—	316 lm	Black	PDF ↗
AL-50-24-7-RGB-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Â°	7.2 W/m	RGB	—	316 lm	Anodised grey	PDF ↗
AL-50-24-7-RGB-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Â°	7.2 W/m	RGB	—	316 lm	Black	PDF ↗
AL-50-24-7-RGB-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Â°	7.2 W/m	RGB	—	316 lm	Anodised grey	PDF ↗
AL-50-24-7-RGB-A002M-BK-OPA-LEC-0M2-1010	Opal	120Â°	7.2 W/m	RGB	—	234 lm	Black	PDF ↗
AL-50-24-7-RGB-A002M-AG-OPA-LEC-0M2-1010	Opal	120Â°	7.2 W/m	RGB	—	234 lm	Anodised grey	PDF ↗
AL-50-24-10-RGBW027-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Â°	9.6 W/m	RGBW-2700K	—	526 lm	Black	PDF ↗
AL-50-24-10-RGBW027-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Â°	9.6 W/m	RGBW-2700K	—	526 lm	Anodised grey	PDF ↗
AL-50-24-10-RGBW027-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Â°	9.6 W/m	RGBW-2700K	—	526 lm	Black	PDF ↗
AL-50-24-10-RGBW027-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Â°	9.6 W/m	RGBW-2700K	—	526 lm	Anodised grey	PDF ↗
AL-50-24-10-RGBW027-A002M-BK-OPA-LEC-0M2-1010	Opal	120Â°	9.6 W/m	RGBW-2700K	—	389 lm	Black	PDF ↗
AL-50-24-10-RGBW027-A002M-AG-OPA-LEC-0M2-1010	Opal	120Â°	9.6 W/m	RGBW-2700K	—	389 lm	Anodised grey	PDF ↗
AL-50-24-2-030-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Â°	2.4 W/m	3000K	CRI 95	250 lm	Black	PDF ↗
AL-50-24-2-030-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Â°	2.4 W/m	3000K	CRI 95	250 lm	Anodised grey	PDF ↗
AL-50-24-2-030-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Â°	2.4 W/m	3000K	CRI 95	250 lm	Black	PDF ↗
AL-50-24-2-030-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Â°	2.4 W/m	3000K	CRI 95	250 lm	Anodised grey	PDF ↗
AL-50-24-2-030-A002M-BK-OPA-LEC-0M2-1010	Opal	120Â°	2.4 W/m	3000K	CRI 95	185 lm	Black	PDF ↗
AL-50-24-2-030-A002M-AG-OPA-LEC-0M2-1010	Opal	120Â°	2.4 W/m	3000K	CRI 95	185 lm	Anodised grey	PDF ↗
AL-50-24-10-03035-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Â°	9.6 W/m	3000K-3500K	CRI 95	1,004 lm	Black	PDF ↗
AL-50-24-10-03035-A002M-AG-SQO-LEC-0M2-1010	Square opal	120Â°	9.6 W/m	3000K-3500K	CRI 95	1,004 lm	Anodised grey	PDF ↗
AL-50-24-10-03035-A002M-BK-RDO-LEC-0M2-1010	Round opal	120Â°	9.6 W/m	3000K-3500K	CRI 95	1,004 lm	Black	PDF ↗
AL-50-24-10-03035-A002M-AG-RDO-LEC-0M2-1010	Round opal	120Â°	9.6 W/m	3000K-3500K	CRI 95	1,004 lm	Anodised grey	PDF ↗
AL-50-24-10-03035-A002M-BK-OPA-LEC-0M2-1010	Opal	120Â°	9.6 W/m	3000K-3500K	CRI 95	743 lm	Black	PDF ↗
AL-50-24-10-03035-A002M-AG-OPA-LEC-0M2-1010	Opal	120Â°	9.6 W/m	3000K-3500K	CRI 95	743 lm	Anodised grey	PDF ↗
AL-70-24-10-03035-A002M-BK-SQO-LEC-0M2-1010	Square opal	120Â°	9.6 W/m	3000K-3500K	CRI 95	1,008 lm	Black	PDF ↗
AL-70-24-10-03035-A002M-AG-SQO-LEC-0M2-1010							Anodised	